



Description:	Side Chair
Model Number:	WC-13600
Model Name:	Oswald
Width:	21"
Height:	33"
Depth:	25"
Seat Width:	21"
Seat Height:	19"
Seat Depth:	18.5"
Arm Height:	NA
Seat Cushion Style:	Tight
Seat Cushion Content:	1.8 Density 35# compression Ultracell HR - High Resilience Polyurethane foam. 3/4 oz blended fiber overlay.
Seat Support:	Coated sheet webbing applied to the rails. Provides uniform seat foam support and superior seat deck life.
Back Cushion Style:	Tight
Back Cushion Content:	1.1 density 22# compression Ultracell Polyurethane foam. 3/4 blended fiber overlay.
Frame:	Frames stocks are harvested from certified sustainable sources . Frame is constructed in European Beech lumber with all parts being cut and machined in the United States. All stress joints to be connected utilizing one of the following, Double Doweled, or motise and tenon joinery. Corner block are finger jointed into seat rails. Blocks are screwed and glued in place. Glue is polyvinyl acetate. Frames finished in 14 step process utilizing a catalyzed conversion varnish sealer and top coat. Conversion varnish offers superior moisture resistance, cleaner / chemical resistance and surface strength. The coating includes an anti-microbial agent as well as a UV Inhibitor.
Finish:	
Warranty:	Kellex warrants exposed wood-framed seating against defects in materials and workmanship, under conditions of normal use and service, for 6 years from the date of purchase.
Additional Notes:	

www.kellex.com